

STANDARD HORIZON

How to Request the User MMSI and ATIS Reset Code




In order to re-set the User MMSI and ATIS Code in the HX890E/HX891BTE you need to obtain a Request Code from within your HX890E/HX891BTE software and then submit it to Standard Horizon with additional information.

The process is as follows:

Obtain the Request code from within the HX890E/HX891BTE Software:



1. Press the [**CH**▼]/[**CH**▲] key to select “**USER MMSI**” or “**ATIS CODE**”, then press the [**SELECT**] soft key.
The **RESET** screen will appear.
2. Press the [**SELECT**] soft key again.
The request code will be displayed.



NOTE

When resetting both “**USER MMSI**” and “**ATIS CODE**”, both request codes are required.

To request the Reset Code from Standard Horizon:

Please email the following information to Standard Horizon:

- Model name
- Serial number
- Current MMSI number or/and ATIS code
- Request codes for the MMSI number or/and the ATIS code (as obtained above)

Contact Information:

EUROPE

E-mail: service@standardhorizon.co.uk

USA/CANADA

E-mail: marinetech@yaesu.com


STANDARD HORIZON

How to Reset the User MMSI and ATIS Number


Here is the procedure for resetting the USER MMSI and ATIS codes in your HX890E after obtaining the reset codes from Standard Horizon.




1. Press the [CH▼]/[CH▲] key to select “USER MMSI” or “ATIS CODE”, then press the [SELECT] soft key.




3. Press the [CH▼]/[CH▲] key to select “PASSWORD”, then press the [SELECT] soft key.
The password input screen will appear.



4. Input the acquired reset code.
 - Select the character with the [CH▼]/[CH▲]/[◀]/[▶] keys
 - Press the [SELECT] soft key to input the character
 - Press the [SELECT] soft key to select “←” or “→” on the screen to move the cursor.
 - Press the [SELECT] soft key to select “Delete” on the screen to delete the selected character



5. Press the [FINISH] soft key.
If the reset is successful, “COMPLETE!” will appear on the screen.
If the error message is displayed, input the reset code again.



6. Press the [OK] soft key to return to setup screen.

PLEASE NOTE

The acquired reset code is only valid for one use, if you need to reset the MMSI or ATIS number again, you will have to request a new reset code.